fi-6130/fi-6230 Color Duplex Workgroup Scanners

Enhanced for the ultimate in performance and reliability

- Fast, 40ppm / 80ipm scanning in monochrome and grayscale
- Exceptional 300 dpi color scanning at 30ppm / 60ipm
- Advanced paper handling technology for the ultimate in feeding reliability
- ▶ Robust 50-page Automatic Document Feeder (ADF) with enhanced hard embossed card scanning
- Comes with Kofax® VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro







Discover a new level of front-office productivity with the fi-6130 and fi-6230 documents scanners Enhanced with innovative features, the Fujitsu fi-6130 and fi-6230 scanners offer outstanding price/performance value in a compact footprint, conserving both space and budget. With duplex scanning performance of up to 80 images per minute in monochrome and grayscale, the fi-6130 and fi-6230 also delivers uncompromised high-resolution performance of up to 60 images per minute in color at an astounding 300 dpi. Engineered with one of the most advanced paper separation features in their class, the fi-6130 and fi-6230 are the first workgroup scanners equipped with reversing roller technology*, resulting in exceptional feeding reliability for an even wider variety of document weights. Furthermore, the automatic document feeder (ADF), capable of scanning document up to 10 feet long, is also robust enough to feed up to three hard cards continuously or an embossed card up to 1.4 mm in thickness. Additionally, the fi-6130 and fi-6230 harmoniously combines the security of Ultrasonic Double Feed Detection with the efficiency of Intelligent MultiFeed Function (iMFF) so that intentional double-feeds, such as a taped receipt or sticky note, can be manually bypassed while double-feed detection is enabled.

Fully Loaded One Box Solution.

Fujitsu fi-6130 and fi-6230 workgroup scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-ofmind. For full details on the Limited Warranty and on all service programs, go to www.lmageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc. Fujitsu Computer Products of America, Inc. is a subsidiary of Fujitsu Limited, a leading provider of customer-focused IT and communications solutions for the global marketplace. FCPA provides innovative solutions for the U.S. marketplace. Current product and service offerings include high performance hard disk drives, scanners and scanner maintenance, palm vein recognition technology, 10Gb Ethernet switches and degaussers.

Fujitsu Computer Products of America, Inc.

http://us.fujitsu.com/fcpa 1255 East Arques Avenue Sunnyvale, CA 94085-4701. (800) 626-4686 (408) 746-7000 info@fcpa.fujitsu.com

©2008 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks and The Possibilities are Infinite is a trademark of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Translations, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. As an ENERGY STAR® Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a U.S. registered trademark of the t istered trademark. All other trademarks are the property of their respective owners.

All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs.

		1	3 - 1		
			fi-6130/fi-6230		
Functional S					
Image Sensor	Type	fi-6130	Color Charge Coupled Device (CCD) x 2		
		fi-6230	Color Charge Coupled Device (CCD) x 3		
Light Source			White cold cathode discharge lamp		
Optical Resolution			600 dpi		
Output Resolution ¹ Color (24 bit) Grayscale (8 bit)		Color (24 bit)	50 to 600 dpi		
		Grayscale (8 bit)	(adjustable by 1 dpi increments, 1200 dpi) ²		
		Monochrome			
Output Format			Color: 24 bit, 8 bit/4 bit; Graysca	Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 b	
AD Converter			1024 levels (10 bit)		
Output Mode			Dither / En	ror diffusion	
Scanning sp	eeds				
Output (Letter/A4 size) ³			Simplex Duplex		
Color ⁴		200 dpi	30 ppm	60 ipm	
		300 dpi	30 ppm	60 ipm	
Grayscale ⁴ /		200 dpi	40 ppm	80 ipm	
Monochrome		300 dpi	30 ppm	60 ipm	
ADF Capacity ⁵			50 Sheets (letter/A4, 20 lb.)		
Document size	e ADF	minimum	2 in. x 3 in. (52mm x 74mm)		
	ADF	maximum	8.5 in. x 14 in. (Legal)		
	Lone	g Document	8.4 in. x 122 in. (10 feet) ⁹		
		ped (fi-6230 only)	8.5 in x 11.69 in. (216mm x 297mm)		
ADF Feeding	Norr		11 to 56.2 lb. (41 to 210g/m²)		
Paper Weight		sheets	34 to 56.2 lb. (127 to 210g/m²)		
(Thickness)	Card ⁶ (1.4 mm) ⁷		Portrait and Landscape feedings		
Interface			USB 2.0 / USB 1.1 (B type connector)		
Physical Spe	cifica	tions		(= 1) 10 10 10 10 10 10 10	
Power requirements			100 - 240 VAC, 50/60 Hz		
Power	fi-61	30		p: less than 6.2W)	
consumption				p: less than 6.2W)	
Dimensions	fi-61	30	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)		
(WxDxH) ¹⁰	fi-62		11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)		
Weight	fi-61		9.24 lb. (4.2 kg)		
	fi-62		19.36 lb. (8.8 kg)		
Environmenta	nvironmental Compatibility ¹¹		ENERGY STAR® and RoHS		
Operating		perature	42° to 95°F (5° to 35°C)		
Environment		tive humidity		on-condensing)	
Inbox Conten			TWAIN, ISIS™, USB cable, AC adapter		
Bundled Software			Adobe® Acrol	pat® Standard.	
			Kofax® VBS® Professi	Kofax® VRS® Professional and ScandAll Pro	
Options			Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6230		
OS Support			Microsoft® Windows® 2000 Profess		
				Microsoft® Windows Server™ 2003 (32 bit/64 bit) /	
			Microsoft® Windows Vista™ (32 bit/64 bit)		
Feed Detection Features				eed Detection Sensor	
				nction (Manual Bypass)	
Other Features				nning Capability,Long Documer	
			Scanning, Automatic Color Recognition, Automatic		
			Paper-Size Detection, Automatic De-skew Correction,		
			Selectable White & Black Background (in ADF only).		
Limited Warranty			One-year. Advance Exchange program also available; restrictions appl		
			For full details, visit www.lmagingService.com or call (800) 626-4686		
Service Options			Post-Warranty: Advance Exchange Plus; restrictions apply		
			Consumables: ScanAid™ kit. For full details,		
				com or call (800) 626-4686.	
Part Number	fi-61	30		40-B055	
I all Nulliber	11-01	00	FAU332	+0-0000	

- Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpl or higher). Actual scanning speeds are affected by data transmission and software processing times.
- Scanning limitations broug Actual scanning speeds a JPEG compressed figures

fi-6230

- * JPEG compressed figures. * Maximum paper weight. * Supports ISO/2810 expending upon paper weight. * Supports ISO/2810 embossed cards * Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm). * Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm). * Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability) * The scanning of documents that exceed 35 inches in length will be limited to using TWAIN at 200 dpi or less. * Excluding the ADF paper chute and stacker. * EPTU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).







PA03540-B555



ADOBE ACROBAT 8 STANDARD





^{*} Statement true as of March 2008